

Features

- 2 proportional PWM spreader outputs (spinner, conveyor +reverse)
- 8 proportional PWM joystick outputs (plow raise, hoist lower ect.)
- Full transient suppression on all outputs
- Parameter based programming
- Programming key to protect calibration values
- 9 spinner and 9 conveyor settings
- Conveyor reverse function
- Material calibration for open and closed loop operation
- Pause and blast integrated into the selector dials
- Pause and blast indicators
- Remote pause and blast actuation
- 4 axis joystick capability (Hoist and Plow control)
- Full transient suppression on all outputs
- User defined status indicators with backlight legends
- Remotely located valve driver and microcontroller for a compact installation

Advanced Functions

- Large backlight LCD display
- On-screen descriptions of parameters
- Parameter adjustment through tactile buttons
- Adjustable blast setting
- On screen vehicle speed calibration
- 5 operator modes
- Auto-nulling in closed loop operation
- Audible error indication with text explanation
- Current compensated and protected outputs
- Solenoid and cable failure detection
- Backlit LCD display
- Hall effect joystick with deadman interlock
- On-screen joystick nulling
- Available firmware upgrades via PC link

Rexroth CS 425
Integrated Spreader and Joystick Console

03.2012



Two function, programmable controller for granular application with four function joystick

Microcontroller (RC-6/9) Electrical and Environmental Specifications

Spurious interference	(Motor vehicle directive 95/54/EG)	100 V/m max. 70 v
Load Dump	Operating	-40...80 °C
	Storage	-40...105 °C
Vibration Resistance	Sinusoidal (IEC 60066-2-6)	10 g / 57...2000 Hz
	Random (IEC 60066-2-36)	0.05 g ² / Hz; 30 min per axis
Shock Resistance	Transport (IEC 60068-2-27)	15g / 11ms; 3 x in each direction/axis (pos./neg.)
	Continuous (IEC 60068-2-29)	25 g / 6 ms; 1000 x in each direction/axis (pos./neg.)
Resistance	To moisture	95 % (+25 to +55 °C)
	To salt spray (IEC 60068-2-11)	72 h, 35 °C, 5 % NaCl
Type of Protection	(DIN / EN 60529) fitted with mating connector	IP 65

The CS 425 has all the features of the CS 420 controller with the addition of a proportional joystick and 2 auxiliary switch functions. The CS 425 is ideally suited for compact vehicle interiors and applications where a joystick and spreader controller is required.

The proportional joystick has a 4 axis capability, and the console has 2 status indicators for modes. A deadman switch on the joystick handle prevents accidental activation of a function.

The spreader section controls the spinner and conveyor based on vehicle speed and conveyor feedback. Or the unit can be operated as a manual or open loop controller.

Joystick nulling and spreader calibration are performed on screen making setup quick and easy.

© Bosch Rexroth Canada Corp. reserves the right to revise this information at any time and for any reason and reserves the right to make changes at any time, without notice or obligation, to any of the information contained in this piece of literature.

Bosch Rexroth Canada
490 Prince Charles Drive S
Welland, ON L3B 5X7
Phone: (905) 735-0510
Toll Free: 1-877-COMPUI-11
info@boschrexroth.ca
www.boschrexroth.ca/cs