

Compu-Spread CS 524

Solids & Auxiliary Device Controller

05.2018



- ▶ **Two function programmable controller, available in Manual, Closed or Open Loop mode, for the controlled application of granular solids in snow and ice controls. The joystick and switch panel can control auxiliary devices.**

The Rexroth CS-524 controller is designed for two axis spreader applications, with manual control of one axis (spinner) and manual, ground speed triggered manual, open or closed loop regulation of the other. A large high contrast solid state display shows the status of all important functions. Two heavily detented knobs are for the Spinner and Conveyor control functions, each with 9 settings. The push buttons integral to the control knobs are for Blast and Pause. Five touch pads below the display are used in the setup mode.

The 2-axis joystick has two modes to support up to 4 on-off double acting cylinder functions, such as Plow and Hoist. Five switches can be used for auxiliary functions.

System setup and calibrations are easily accomplished with on-screen text defined parameters and separate selection buttons. Vehicle speed and material calibration are quickly set with on-screen prompts. Four materials can be set-up. The USB port provides controlled access to event logging and calibration, as well as any firmware upgrades. A serial port for diagnostics and AVL interface is standard.

The CS-524 is built around a 32 bit processor with many advanced features. All components and operating devices are industry proven, fitted into a rugged extrusion

made to withstand the rigours – and temperatures – of winter.

The CS-524 complements the Compu-Spread family of snow and ice control products from Bosch Rexroth. It is ideally suited for the control of the large range of Rexroth hydraulic valves and modules, which find broad usage in these demanding applications.

Features

- 5.5" OLED (organic light emitting diode) display
- On-screen display of storm and season totals
- 2 frequency inputs (ground speed, conveyor)
- 2 proportional, current compensated PWM outputs (programmable dither frequency) for Spinner & Conveyor
- 1 digital output (reverse, air gate or ground speed)
- Dual axis switching joystick with up to 8 outputs
- 5 auxiliary switches (illuminated)
- USB key or password-protected calibration values
- Operating parameters and event data can be retrieved by USB memory stick
- Automatic nulling & material calibration (closed loop only)
- Remote Pause and Blast with detachable cable
- Adjustable Blast setting
- Solenoid and cable failure detection
- Firmware upgradable via USB

Technical Data

General	
Enclosure Material	Extruded aluminum, powder coated
Weight	3.6 lb. mass (1.64 kg)
Size (excluding connectors & joystick)	8.692" x 7.185" x 2.377" (221 x 183 x 60.4 mm)
Mechanical Mounting	"Ram Bracket", size 1-½"
Joystick	"X" Gate, or 360° movement
Electrical	
Power Supply	8-32 VDC
Solenoid Voltage	12 VDC , 2 A maximum (2 x)
Auxiliary Switches (5 x)	2 A; illumination: red, green, amber; custom legend text
Joystick	8 on/off outputs, 2A each, built-in coil suppression
Electromagnetic Compatibility	100v/m load dump ISO7637-2 (2004), pulse 5
RF Immunity	ISO 11452-2 400-1000 MHz, 80% mod. 1 kHz
Conducted Immunity	ISO 7637-2 (2004) System Pulse 1, 2a, 2b, 3b, 4
RF Emissions	CISPR 25:2002-08 30 MHz-1GHz acc. to 72/245/EC EN 55025
Electrostatic Discharge	EN 6100-4-2 ISO 10605 Contact +/- 8kv, air discharge +/- 15kv
Vibration	ISO 16750-3 10-2000 Hz at 58m/s; IEC 60068-2-72 40G for 11 ms
Environmental	
Operating Temperature	-30 ... 85° C
Storage Temperature	-40 ... 85° C
UV Resistance	DIN 75220
Media Resistance	ISO 16750-5
Protection Category	IEC 60529, IP63

* The charts above are for reference and are provided only for general information.

Bosch Rexroth Canada
490 Prince Charles Drive S
Welland, ON L3B 5X7
Phone: (905) 735-0510
Toll Free: 1-877-COMPU-11
info@boschrexroth.ca
www.boschrexroth.ca/cs

© Bosch Rexroth Canada Corp.
This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that our products are subject to natural process of wear and aging. Subject to change.