


Product Information PI_051 2015|07 NXA065S-36V and NXA065S-36V-B – the Intelligent Cordless Wi-Fi Nutrunners



When it comes to the Nexo, the complete controller and the barcode scanner are located on the nutrunner. With the integrated controller, the cordless nutrunners can also be connected directly to superior control systems – without requiring additional hardware in your network. Quite clever – and with a working range up to 65 Nm. In addition, the Nexo series of nutrunners fulfill all requirements for safety-critical tightening jobs in accordance with VDI/VDE2862.

Reliable processes

During each work step, the integrated controller monitors the tightening process and transmits the results over a wireless connection to an access point. In case of a dead spot, it buffers the data and transmits it as soon as the connection with the network has been re-established.

Information at a glance

Users can see the quality of the tightening job immediately and clearly, regardless of their location and the radio connection. This keeps results and information in view at all times.

Precise measuring system

A high-quality monitoring unit for torque and angle of turn is integrated in the nutrunner. A precise action measurement transducer with a practical display that indicates its Nm values ensures highly accurate results.

Browser-based software

The operating software is available online via a webbrowser, e.g. Firefox, and can be used without local installation. Access to the browser-based software is independent of the operating system or terminal device. This simplifies set-up, as no additional software installation is required.



	Working range [Nm]	Max. output drive speed [1/min]	Tool mount	Weight without battery [kg]	Length without battery [mm]	Code	Order no.
A	3.0 - 11	850	3/8" square drive	1.56	442	NXA011S-36V	0 608 842 011
	3.0 - 11	850		1.56	442	NXA011S-36V- B*	0 608 842 012
	3.0 - 15	600		1.56	442	NXA015S-36V	0 608 842 001
	3.0 - 15	600		1.56	442	NXA015S-36V- B*	0 608 842 006
B	9.0 - 30	310	3/8" square drive	1.99	534	NXA030S-36V	0 608 842 002
	9.0 - 30	310		1.99	534	NXA030S-36V- B*	0 608 842 007
	15 - 50	185		2.03	534	NXA050S-36V	0 608 842 003
	15 - 50	185		2.03	534	NXA050S-36V- B*	0 608 842 008
	NEW! 20 - 65	135		2.03	534	NXA065S-36V	0 608 842 013
	NEW! 20 - 65	135		2.03	534	NXA065S-36V- B*	0 608 842 014
C	1.8 - 12	880	1/4" quick-change chuck	1.34	237	NXP012QD-36V	0 608 842 005
	1.8 - 12	880		1.34	237	NXP012QD-36V- B*	0 608 842 010

* with an integrated barcode scanner

Rexroth
Bosch Group

Bosch Rexroth AG
Electric Drives and Controls
Postfach 1161
71534 Murrhardt, Germany
Fornsbacher Str. 92
71540 Murrhardt, Germany
Tel. +49 7192 22-208
Fax +49 7192 22-181
www.boschrexroth.com/tightening